



**SCHOTTKY DIODE MODULE TYPE
600A / 20-100V**

Features

High surge Capability
Types Up to 100V V_{RRM}




Maximum Ratings

Operating Temperature: -55°C to +150 °C
Storage Temperature: -55°C to +150 °C

Dimensions in mm (1 mm = 0.0394")

Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBRA60020CT(R)	20V	14V	20V
MBRA60030CT(R)	30V	21V	30V
MBRA60035CT(R)	35V	25V	35V
MBRA60040CT(R)	40V	28V	40V
MBRA60045CT(R)	45V	32V	45V
MBRA60060CT(R)	60V	42V	60V
MBRA60080CT(R)	80V	56V	80V
MBRA600100CT(R)	100V	70V	100V





Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current (Per pkg)	I _{F(AV)}	600A	T _C = 100 °C
Peak Forward Surge Current (Per leg)	I _{FSM}	4000A	8.3ms, half sine
Maximum Instantaneous Forward Voltage (Per leg) 20V~45V 50V~60V 80V~100V	V _F	0.70V 0.75V 0.84V	I _{FM} =300A; T _J =25 °C
Maximum Instantaneous Reverse Current At Rated DC Blocking Voltage (Per leg) NOTE (1)	I _R	1 mA 10 mA 50 mA	T _J = 25 °C T _J = 100 °C T _J = 150 °C
Maximum Thermal Resistance Junction To Case (Per leg)	R _{θjc}	0.28°C/W	

NOTE :

(1) Pulse Test: Pulse Width 300 μ sec, Duty < 2%






Figure.1-Typical Forward Characteristics




Figure.2-Forward Derating Curve




Figure.3-Peak Forward Surge Current





Figure.4-Typical Reverse Characteristics





Disclaimer

DACO Semiconductor reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein.

DACO Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does DACO Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.

Purchasers is responsible for its products and applications using DACO Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by DACO Semiconductor. "Typical" parameters which may be provided in DACO Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts.

DACO Semiconductor products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of DACO Semiconductor's product can reasonably be expected to result in personal injury, death or severe property or environmental damage. DACO Semiconductor accept no liability for inclusion and/or use of DACO Semiconductor's products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Purchasers buy or use DACO Semiconductor products for any such unintended or unauthorized application, Purchasers shall indemnify and hold DACO Semiconductor and its suppliers and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that DACO Semiconductor was negligent regarding the design or manufacture of the part.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of DACO Semiconductor Co., Ltd.